

What's New at Central!



**BOOK A
FREE DEMO
NOW**

Call us on
1300 347 347

**Custom
Branding
Available**



Camill Electric Utility Vehicles

Meet the fleet of Camill Electric Utility Vehicles. They are environmentally friendly and are packed with features to get the job done - whether it's heavy moving, pressure cleaning, outdoor sweeping or rubbish removal.



Camill Sidewalk Sweeper | S13

Code: CAM-S13



Camill Electric Sweeper | S16

Code: CAM-S16S



Battery Specification	48V 100Ah
Motor	48V 1.5kW DC brushless motor
Max. Driving Speed	≤30km/h
Braking Distance	<2m
Turning Radius	2m
Gradeability	>15%
Wheelbase	1340mm
Dimensions	2200mmL x 1480mmW x 1850mmH
Curb Weight	479kg
Main Brush Width	700mm x 1 piece
Side Brush Diameter	500mm x 3 pieces
Sweeping Width	1380mm
Water Pump Flow Rate	3.8L/min
Water Tank Capacity	60L
Hopper Capacity	120L
Maximum Work Productivity	10000m ² /h
Operation Hour	5h

Battery Specification	48V 220Ah
Motor	48V 5kW AC asynchronous motor
Max. Driving Speed	≤22km/h
Braking Distance	<5m
Turning Radius	5m
Gradeability	>15%
Wheelbase	1445mm
Dimensions	2700mmL x 1500mmW x 1800mmH
Curb Weight	950kg
Main Brush Width	720mm x 1 piece
Side Brush Diameter	650mm x 2 pieces (Front brush) 500mm x 2 pieces (Brush behind)
Sweeping Width	1800mm
Water Pump Flow Rate	3.8L/min
Water Tank Capacity	100L
Hopper Capacity	120L
Maximum Work Productivity	12000m ² /h
Operation Hour	6-7h

Camill Electric Road Sweeper | S19

Code: CAM-S19



Camill Street Sweeper | S22

Code: CAM-S22



SWEEPERS

Camill Electric Utility Vehicles

Battery Specification	48V 220Ah
Motor	48V 5kW AC asynchronous motor
Max. Driving Speed	≤22km/h
Braking Distance	<8m
Turning Radius	6m
Gradeability	>15%
Wheelbase	2066mm
Dimensions	3840mmL x 1800mmW x 1980mmH
Curb Weight	1500kg
Main Brush Width	720mm x 1 piece
Side Brush Diameter	650mm x 4 pieces
Sweeping Width	1900mm
Water Pump Flow Rate	3.8L/min
Water Tank Capacity	200L
Hopper Capacity	240L Standard Bin
Maximum Work Productivity	14000m ² /h
Operation Hour	6-7h

Battery Specification	48V 400Ah
Motor	72V 7.5kW AC asynchronous motor
Max. Driving Speed	20km/h
Turning Radius	≤5m
Wheelbase	2260mm
Dimensions	3850mmL x 1825mmW x 2155mmH
Curb Weight	2250kg
Main Brush Width	740mm x 1 piece
Main Brush Diameter	500mm x 1 piece
Side Brush Diameter	600mm x 4 pieces
Sweeping Width	2000mm
Water Pump Flow Rate	3.8L/min
Water Tank Capacity	300L
Hopper Capacity	1200L



Camill 2 Seater Garbage Truck | S4DHP

Code: CAM-S4DHP



Camill Sideload Garbage Vehicle | Y40

Code: CAM-Y40



Battery	12 x 6V maintenance-free battery
Motor	7.5kW AC motor
Controller	Toyota AC controller 80L440B—440A
Charger	Off-board 72V/25A

Passenger Capacity	2 person
Range	80-100km
Max. Speed at Full Loading	32km/h
Min. Turning Radius	5.2m
Max. Climbing Ability (Loaded)	20%
Loading Capacity	1000kg
Brake Distance	4m

Overall Dimensions	4920mmL x 1600mmW x 2025mmH
Min. Ground Clearance	180mm
Wheelbase	1200mm/1230mm
Cargo Box Dimension	3200mmL x 1480mmW x 265mmH

Battery Specification	72V 220Ah
Motor	72V 7.5kW AC asynchronous motor

Range	100km
Max. Driving Speed	≤35km/h
Braking Distance	≤5m
Turning Radius	5m
Gradeability	30%

Dimensions	3740mmL x 1450mmW x 2020mmH
Curb Weight	1790kg

Hopper Volume	3.5m ³
Compression Ratio	1:2
Lifting Capacity	120L & 240L standard bin at a time



Camill Compression Garbage Truck | Y48

Code: CAM-Y48



Camill Compression Garbage Truck | Y48E

Code: CAM-Y48E



GARBAGE TRUCKS

Camill Electric Utility Vehicles

Battery Specification	72V 220Ah
Motor	7.5kW AC asynchronous motor
Range	100km
Max. Driving Speed	≤35km/h
Braking Distance	≤5m
Turning Radius	6m
Gradeability	30%
Wheelbase	2300mm
Dimensions	4360mmL x 1430mmW x 2000mmH
Curb Weight	2080kg
Hopper Volume	3.1m ³
Compression Ratio	1:2
Lifting Capacity	120L & 240L standard bin at a time

Battery Specification	72V 200Ah
Motor	72V 7.5kW three phase AC asynchronous motor
Range	118km
Max. Driving Speed	35km/h
Braking Distance	5m
Turning Diameter	9m
Gradeability	30%
Wheelbase	2250mm
Dimensions	4565mmL x 1560mmW x 2390mmH
Curb Weight	2380kg
Hopper Volume	3.6m ³
Compression Ratio	1:2
Lifting Capacity	2 x 120L standard bin 2 x 240L standard bin 1 x 660L standard bin 1 x 1100L standard bin

Pump Flow	5-7L/min
Pump Pressure	0-7Mpa
Length of high pressure hose	15m
Water Tank Volume	45L

Camill Electric Transport Vehicle | Y10

Tray Model | Code: CAM-Y10



Camill Electric Transport Vehicle | Y11

Enclosed Model | Code: CAM-Y11



Battery Specification	72V 220Ah
Motor	72V 5kW AC asynchronous motor
Max. Driving Speed	35km/h
Braking Distance	<5m
Turning Radius	<6m
Gradeability	>30%
Wheelbase	2150mm
Dimensions	4110mmL x 1380mmW x 2020mmH
Curb Weight	1460kg
Hydraulic Tailboard Rising Time	8s
Hydraulic Tailboard Falling Time	15s
Loading Dustbin	6 x 240L Standard Dustbin
Compartment Type	Open
Compartment Size	2530mm x 1380mm x 600mm (Fence Height)

Battery Specification	72V 220Ah
Motor	72V 5kW AC asynchronous motor
Max. Driving Speed	35km/h
Braking Distance	<5m
Turning Radius	<5m
Gradeability	>30%
Wheelbase	1530mm
Dimensions	3200mmL x 1380mmW x 2020mmH
Curb Weight	1560kg
Hydraulic Tail Plate Rising Time	8s
Hydraulic Tail Plate Falling Time	15s
Loading Dustbin	6 x 240L Standard Dustbin
Compartment Type	Closed
Compartment Size	2530mm x 1380mm x 1260mm

Camill Electric Transport Vehicle | S2BHY6

Tray Model | Code: LT-S2BHY6



Battery	12 x 6V maintenance-free battery
Motor	7.5kW AC motor
Controller	Toyota AC controller 80L440B—440A
Charger	Off-board 72V/25A
Passenger Capacity	2 person
Range	80-100km
Max. Speed at Full Loading	32km/h
Min. Turning Radius	5.2m
Max. Climbing Ability (Loaded)	20%
Loading Capacity	1000kg
Brake Distance	4m
Overall Dimensions	4015mmL x 1483mmW x 1900mmH
Min. Ground Clearance	180mm
Wheelbase	1200mm/1230mm
Cargo Box Dimension	2615mmL x 1430mmW x 550mmH

Camill Electric Transport Vehicle | S2BHX

Enclosed Model | Code: LT-S2BHX



Battery	8 x 6V maintenance-free battery
Motor	5kW AC motor
Controller	AC Controller 48M—350A
Charger	Off-board 48V/25A
Passenger Capacity	2 person
Range	80-100km
Max. Speed at Full Loading	28-32km/h
Min. Turning Radius	5.2m
Max. Climbing Ability (Loaded)	15%
Loading Capacity	1000kg
Brake Distance	4m
Overall Dimensions	3958mmL x 1496mmW x 1985mmH
Min. Ground Clearance	180mm
Wheelbase	1200mm/1300mm
Cargo Box Dimension	2598mmL x 1426mmW x 1256mmH

Camill Electric Transport Vehicle | S2DCH

Tray Model | Code: CAM-S2DCH



Battery	5 x 12V maintenance-free battery
Motor	5kW AC motor
Controller	Toyota AC Controller 80L—330A
Charger	On-board 60V/25A
Passenger Capacity	2 person
Range	110-130km
Min. Turning Radius	3.5m
Max. Climbing Ability (Loaded)	20%
Loading Capacity	585kg
Brake Distance	4m
Overall Dimensions	3070mmL x 1370mmW x 1695mmH
Min. Ground Clearance	150mm
Wheelbase	2110mm
Cargo Box Dimension	1550mmL x 1300mmW x 870mmH

Camill Sidewalk Pressure Washer | Q3

Code: CAM-Q3



Battery Specification	48V 100Ah
Motor	48V 1kW DC brushless motor
Max. Driving Speed	≤25km/h
Braking Distance	<4m
Turning Radius	<3m
Gradeability	20%
Wheelbase	1600mm
Dimensions	2220mmL x 1250mmW x 1780mmH
Curb Weight	360kg
Water Pump Flow Rate	5-7L/min
Water Pump Pressure	5-7Mpa
Water Tank Volume	0.27m ³
Washing Width	5-6m
Range of High Pressure Water Gun	7-8m
Side Brush Diameter	620mm
Working Hours	5-6h

Camill High Pressure Wash Truck | Q9

Code: CAM-Q9



Battery Specification	72V 450Ah
Motor	72V 7.5kW AC asynchronous motor
Max. Driving Speed	≤35km/h
Braking Distance	≥5m
Turning Radius	≤5m
Gradeability	30%
Wheelbase	2240mm
Dimensions	4300mmL x 1420mmW x 2100mmH
Curb Weight	1920kg
Water Pump Flow Rate	30L/min
Water Pump Pressure	0-20Mpa
Water Tank Volume	1.2m ³
Washing Width	>10m
Range of High Pressure Water Gun	15m
Working Hours	4-5h

Contact all branches

p: **1300 347 347** | e: sales@centralcleaning.com.au
www.centralcleaning.com.au

Victoria | New South Wales | Tasmania | South Australia | Queensland | Western Australia



CAMILL



electric